

# 11-21 Info letter **CAPROWAX P** Colour **Masterbatches**

Ladies and gentlemen,

October 2021

gladly I would like to inform you the latest of **CAPROWAX P™**- Masterbatches.

## Universal colour application of biopolymer/biocomposites with CAPROWAX P Masterbatches

The palette of **CAPROWAX P™** Masterbatches is changed now to the eco-friendly, calcined, soil similar, pigmentlike Kaolin (FK) as a white pigment. With compostable, waterproof carrier material **CAPROWAX P™ 6006-C65** (intermediate) enable an eco-friendly colouration with soil similar composition of pigments. Titanium Dioxide will be used in exceptional cases only strong reduced. The biomineral, natural Calcium Calcite, is used as a white pigment with gentle covering brightening and soil improving properties **CAPROWAX P™**- carrier material consist of aliphatic, home / industrial compostable certified polyester and modified, readily biodegradable, renewable, GMO-free plant oil.

## **Masterbatches are suited for universal colouration of Bioplastics / Blends / Biocomposites / Filaments:**

**PLA, PBS, PHA, PCL, CAPROWAX P™ / Blends / BioMineralComposites, Polysaccharide/ Derivates, PVAc/Bioplastic-Blends, PVOH, Bio-NFC/WPC, Bio-UPR, Bio-TPE and NIPU.**

Low-dusty incorporated in a compostable carrier material pigments are:

- calcined pigmentlike Kaolin (white pigment)
- natural, biomineral Calcite (dull white pigment)
- biobased vegetable Carbon (black pigment)
- harmless inorganic pigments of synthetic, aniline free production
- chromatic / achromatic as pearlescent pigments

## **Masterbatches for soil improvement:**

**QX** = biobased carbon black, Lava-Powder, soil improver

**BM** = BioMineral, natural Calcite, acid-binding and soil similar

**FK** = calcined Kaolin, compost friendly

for translucent, covering, achromatic and pearlescent colouration.

They are lightfast, non-migratory, temperature stable, insoluble in water, comparable with natural, mineral pigments and already mineralised.

Masterbatch pellets are added to different bioplastics in a range of 0,5-6%.

Processing range at 90-200°C, short time up 220°C.

In coloured final products content of each separate pigment is ≤1%.

In the course of composting the brown to black colour of compost or humus change over to the coloured bioplastic and the colourful appearance disappears.

Colourations with natural, bio-mineral Calcium Carbonate-Masterbatches support biogenic weathering in soil and waters.

Coloured bioplastics comply the specifications of DIN EN 13432.

Kind regards

A. Dinkelaker

**Albrecht Dinkelaker**

Polymer- and Product Development

Talstrasse 83

D 60437 Frankfurt am Main

**Ideas** **increase to** **pellets**